

ON-SITE OXYGEN GENERATOR

DOCS 200

- **Medical Configuration**
 Superior Reliability - Easy Serviceability
 Modular and Turn-Key System For Easy Installation



Characteristics	Value / Description
Discharge flow rate	200 lpm 12 m ³ per hour 425 scfh 840 lbs per day 380 kg per day
O ₂ purity @ discharge flow rate	93% +/- 3%
O ₂ output pressure	20 – 100 psig 1.4 – 6.9 barg
Operating temperature	0°F to 120°F -18°C – 49°C
Power requirements Site power source Plant	380/460 VAC +/- 10%, 50/60 Hz +/- 3%, 3-Phase, 60/50 Ampere 380/460 VAC , 50/60 Hz, 3-Phase, 42/36 FLA
Average power consumption	7.7 kW at 20 psig (1.4 barg) output pressure 8.0 kW at 55 psig (3.8 barg) output pressure 8.4 kW at 100 psig (6.9 barg) output pressure
Process outlet connection	1/2" Internal NPT Fitting
Unit footprint dimensions (nom.) Crated dimensions (nom.)	72" L x 85" W x 66" H 183 cm L x 216 cm W x 169 cm H 82" L x 96" W x 79" H 208 cm L x 244 cm W x 201 cm H
Unit weight (nom.) Crated Weight (nom.)	3,148 lbs 1428 kg 4,200 lbs 1907 kg
Average scheduled maintenance cost	\$120 – \$150 per month
Average operating cost @ 55 psig	\$0.20 – \$0.27 per 100 scf \$0.07 – \$0.10 per m ³
Additional available options	Remote monitoring & diagnostics suite 4-20 mA Communication to external controller (0-10V standard) Mass flow control assembly Automatic sleep mode feature for low-demand situations Platinum 3 plus 10 Warranty

¹ Performance parameters stated at standard conditions (59°F 14.7 psia 0% RH | 15°C 101.325kPa 0% RH). Operation in atypical conditions may affect performance. For more information, please consult with your PCI technical representative.

² Available in CE compliant and FDA cleared configurations.

³ Electrical enclosure cUL listed